

#### **Product Bulletin**

Product Name: Aquastrip BCA 10 Product Code: 2570011 Revision Date: December 20, 2023

# Aquastrip® BCA 10

Aquastrip BCA 10 is primarily used as a paint stripping additive designed to increase the alkalinity of paint stripping solutions, to improve the effectiveness of mild alkaline paint strippers on hard to remove powder coat and e-coat materials. Aquastrip BCA 10 can also be used as a paint stripper to remove zinc-rich dip spin coatings, from ferrous substrates.

# **Features & Benefits**

| Liquid concentrate | Easy tank side additions         |
|--------------------|----------------------------------|
| High pH            | Increases the alkalinity of mild |
|                    | paint stripping solutions        |

# **Typical Applications**

- Removal of powder paints
- Removal of lacquers and urethane coatings.

# **Operating Conditions**

(Soak Tank)

| 100an ramy    |                                |
|---------------|--------------------------------|
| Concentration | Full strength                  |
| Temperatures  | 100°F – 180°F                  |
| Time          | As required                    |
| Agitation     | Recommended                    |
| Equipment     | Steel or stainless steel tanks |

#### Notice

Before using this material, read and understand OSHA Safety Data Sheet for Aquastrip BCA 10. Specific instructions and precautions should be followed to assure correct use and personal safety.

### **Titration Method**

- 1. Pipette 2 mL sample into a 250 mL beaker containing 50 mL of distilled water.
- 2. Add the magnetic stir bar and place the beaker on the stir plate.
- 3. Turn on the stir plate and secure the pH probe in the solution, keeping the probe end away from the stir bar.







#### **Product Bulletin**

Product Name: Aquastrip BCA 10 Product Code: 2570011 Revision Date: December 20, 2023

- 4. Titrate with 0.5 N Hydrochloric Acid to a pH endpoint of 7.0.
- 5. Record mL used.

Calculation

Concentration = mL 0.5 N HCl x 4.93

# **Waste Disposal**

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

## Our People. Your Problem Solvers.

For more information on this process, please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**<sup>136</sup>.



